



# **2MP Dual Light Camera**

## **Dual-light Dome Coaxial Camera HX Series**

### AHC-HX5320PTA-IR2R-AT

#### Introduction


AHC-HX5320PTA-IR2R-AT is a Dual-light Dome Coaxial Camera, suitable for places with low or no light conditions and high definition image quality, such as roads, warehouses, underground parking lots, bars, pipelines, parks, etc.











#### **Main Features**



HD Lens





Coaxial control Coaxial Upgrade Double light alert



Zero Delay



**Electronic Shutter** 





Multiple signal

outputs

Infrared night vision



Coaxial Audio (Optional)





#### **Product Parameters**

#### Model AHC-HX5320PTA-IR2R-AT

#### Camera

Sensor 1/3" low illumination CMOS sensor

Signal AHD/TVI/CVI@2MP

Min.illumination Color:0.01Lux @(F1.2,AGC ON); 0 Lux with IR

B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR

**Shutter time** 1/50(1/60)s to 1/10,000 s

Lens HD lens 2.8mm/6mm/3.6mm

Lens mount M12

Day&night IR cut filter with auto switch

Max reolution 1920\*1080

#### General

**Temperature** -10 °C-+60 °C

**Humidity** 10%-90% RH

Power supply DC12V±10%

IR range 2 array lamps ,2 white light "IR2":20-30 meters

Consumption MAX 3W

Material ABS plastic

Ingress Protection N/A

 Weight
 Around 300g

 Dimension
 Ф105\*95mm

#### Compression

 Video output
 1Vp-p Composite Output(75Ω/BNC)

 Audio I/O
 1/1, Support coaxial audio (optional)